

PG2056IRC-ZS 5 MP Dual Light varifocal Bullet Network Camera



Key Features

- 1/2.8" Progressive Scan CMOS
- 2592 x 1944@30fps
- HD 2.7 to 13.5mm varifocal lens
- Color: 0.01 Lux @(F1.0, AGC ON),0 Lux with Light
- H.265+,H.265,H.264
- Support PoE
- BLC/3D DNR/HLC/WDR
- Built-in Mic and speaker
- IP66

Specifications

| Specifications | |
|-----------------------------|--|
| Camera | |
| Image Sensor | 1/2.8" Progressive Scan CMOS |
| Min. Illumination | Color: 0.01 Lux @(F1.0, AGC ON),0 Lux with Light |
| White Balance | Auto/Manual |
| Shutter Speed | 1/10 s to 1/10,000 s |
| Day & Night | IR Cut Filter |
| Digital Noise Reduction | 2D/3D DNR |
| WDR | Support |
| Privacy Mask | 4 programmable privacy masks |
| Lens | |
| Focal Length | f=2.7-13.5mm F=1.6-3.3, with IR cut |
| Field of View | Horizontal: 100°- 32° Vertical: 55°- 18° |
| Compression Standard | |



| | |
|------------------------|--|
| Video Compression | Main stream: H.265+,H.265,H.264 Sub-stream: H.265+,H.265,H.264 |
| H.265 Type | Baseline profile/Main profile/High profile |
| H.265+ | Yes |
| Event | |
| Basic Event | Motion Detection |
| Intelligent detection | Human Detection / Vehicle detection |
| Illuminator | |
| Light Range | 30 m |
| LEDS | 4PCS Warm Light LED and 4PCS IR LED |
| Image | |
| Max. Resolution | 2592 x 1944 |
| Main Stream | 30fps@2592 x1944,2560 x 1440,1920 x 1080 |
| Sub-Stream | 30fps@720 x480 /VGA/640x360/480 x360 /CIF |
| Image Enhancement | BLC/3D DNR/HLC/WDR |
| Network | |
| Network Storage | Support Local storage and NFS,NVR,APP Cloud Storage |
| Protocols | HTTP, IPv4, RTSP, DHCP, P2P, RTMP, SMTP, NTP, DNS, FTP, P2P, HIKVISION,ONVIF(Profile S) |
| General Fuction | Built-in Mic and speaker,Privacy Masks, Horizon/Vertical Flip>Password Reset,Upgrade |
| API | ONVIF (Profile S) |
| Simultaneous Live View | Up to 12 channels |
| User/Host | 3 levels: Administrators, Operators and Users |
| Client | HIKVISION NVR,IVMS-4200,AC18PRO,LMS |
| Web Browser | IE, Edge, Chrome, Firefox, Safari |
| Interface | |
| Network Interface | 1 RJ45 10 M/100 M Ethernet, PoE |
| Power | 12V DC |
| Audio IN | Built-in microphone |
| Audio Out | Two-Way audio |
| RS485 | N/A |
| SD Card slot | Max. 256GB |
| General | |
| Web Client Language | 7 languages: Chinese, English, Russian, German, Italian, , Turkish, 한국어 |
| Power | 12V DC, 1.5 A (Max. 10.9 W, including Max. 4 W for IR) PoE (802.3af), 36 to 57V DC, 0.35 A (Max. 12 W, including max. 4 W for IR) |
| Working Environment | Temperature: -10°C~+55°C (14°F~131°F), humidity: 10% ~ 90% |
| Protection Level | IP66 |
| Material | Metal |
| Dimension | 74 x 89 x 240mm |
| Weight | 600g |